

SuperStapler®



TA238B/18-6

NARROW CROWN STAPLER

FASTENER

| NARROW CROWN STAPLES | |
|----------------------------|----------------|
| Length: | 1/2" to 1 1/2" |
| Head Diameter / Thickness: | .044" x .050" |
| Crown Size: | 1/4" |
| Staple Size: | 18 ga. |



SuperStapler®



TA551B/16-11

MEDIUM CROWN STAPLER

FASTENER

| MEDIUM CROWN STAPLES | |
|----------------------|---------------|
| Length: | 1" to 2" |
| Crown Size: | 7/16" |
| Thickness: | .055" x .062" |
| Staple Size: | 16 ga. |



SuperFinisher®



NF235A/23-35

23GA. MICRO PINNER

FASTENER

| MICRO PINS | |
|-----------------|----------------|
| Length: | 1/2" to 1 3/8" |
| Shank Diameter: | .025" |
| Head Diameter: | .025" |
| Wire Size: | 23 ga. |



MAX

BUILDING OUR WORLD 100PSI CONSTRUCTION TOOLS



MAX

MAX USA CORP.

205 Express Street, Plainview, New York 11803
Phone: 800-223-4293 Fax: 516-741-3272
www.maxusacorp.com

SMR# : STF-007 OCTOBER 2019



www.maxusacorp.com

5 Year Limited Warranty



MAX warrants that 100 PSI pneumatic nailers will be free from defects in material and workmanship under normal use for a period of five (5) years from the date of original retail purchase.

The 5 year warranty does not apply to industrial tools and industrial applications.

30 Day Contractor Promise



MAX offers a 30 day no hassle return policy for credit or replacement of MAX 100 PSI construction nailers. Should a contractor, for whatever reason, want to return a MAX nailer listed below,

CN445R3, CN565S3, CN890F2, SN883RH3, SN890CH3/34, SN883CH2/28, CN665D, NF235A/23-35, NF255FA/18, NF565A/16, NF665A/15, TA238B/18-6, TA551B/16-11, SN438J, NF255SF2/18,

The MAX 30 Day Contractor Promise does not apply to industrial applications.

SPECIAL FEATURES OF MAX PROFESSIONAL GRADE TOOLS



Anti-Double fire mechanism (US Patent 5597106)

The tool can be contact or single fired with no adjustments to the tool. Simply pull the trigger then depress the contact arm and tool will contact fire. To single fire, first depress the contact arm, then pull and hold the trigger. Tool can not fire a second nail until trigger is released and tool can cycle. This is a superior safety feature.



Maintenance free end cap filter (US Patent 5637125)

It prevents foreign substances from entering the tool. Internal parts last longer and the inside of the tool is kept clean. The filter has a self-cleaning feature; foreign substances are ejected automatically from the tool when the air hose is disconnected.



Rapid fire trigger valve

This trigger valve is designed for applications where high-speed firing is required. Keep the trigger pulled and depress the contact arm while sliding the tool along the work surface. You can drive about 15 nails or staples per second and improve production efficiency.



Easy jam clearance system

Nail jam is easily cleared just by the flip of a finger. No special tools required.



Tar resistant nose (Patent Pending)

This nose is designed to resist tar from roofing material and reduce cleaning.



Nose magnet

Magnet that holds the last nail in place, preventing nail jam.



Rear exhaust

Rear exhaust can prevent exhaust air from making applications dirty.



Dial adjustable depth control

Dial depth control required no special tools.



Tangle free swivel plug

No more fighting with heavy hoses, no matter what angle the nailer is being held.



Switchable fire mechanism

This Trigger can switch contact or single fired with switch lever.



Rafter hook

For ease of use and easy storage.



Trigger lock lever

This Trigger lock lever allows the trigger to be disabled when not in use.



Air Duster (Patent No. US8393511B2, US7950557B2)

Push this button to disburse air to quickly clear dust and debris from the work surface.



Easy twist adjustable exhaust deflector

Exhaust air can easily be diverted 360° away from user without any tool.

SuperRoofer®



CN445R3 ROOFING NAILER

FASTENER

COIL ROOFING NAILS

| | |
|------------------|----------------|
| Collation Angle: | 15 degrees |
| Length: | 3/4" to 1 3/4" |
| Shank Diameter: | .120" |
| Head Diameter: | .413" |
| Collation Type: | Wire |



SuperSider®



CN565S3 SIDING NAILER

FASTENER

COIL SIDING NAILS

| | |
|------------------|---|
| Collation Angle: | 15 degrees |
| Length: | Wire 1 1/2" to 2 1/2" Plastic 1 1/4" to 2 1/2" |
| Shank Diameter: | .083" to .099" |
| Head Diameter: | .197" to .236" |
| Collation Type: | Wire, Plastic |



SuperFramer®



CN890F2 COIL FRAMING NAILER

FASTENER

COIL FRAMING NAILS

| | |
|------------------|----------------|
| Collation Angle: | 15 degrees |
| Length: | 2" to 3 1/2" |
| Shank Diameter: | .099" to .131" |
| Head Diameter: | .256" to .303" |
| Collation Type: | Wire |



SuperFramer®



SN883RH3 21 DEGREE FRAMING NAILER

FASTENER

FULL ROUND HEAD STICK NAILS

| | |
|------------------|------------------|
| Collation Angle: | 21 degrees |
| Length: | 2 1/2" to 3 1/4" |
| Shank Diameter: | .113" to .148" |
| Head Diameter: | .267" to .295" |
| Collation Type: | Plastic, Paper |



SuperFramer®



SN890CH3/34 34 DEGREE FRAMING NAILER

FASTENER

OFFSET/CLIPPED HEAD STICK NAILS

| | |
|------------------|------------------|
| Collation Angle: | 30 to 34 degrees |
| Length: | 2" to 3 1/2" |
| Shank Diameter: | .113" to .131" |
| Head Diameter: | .256" to .303" |
| Collation Type: | Paper |



SuperFramer®



SN883CH2/28 28 DEGREE FRAMING NAILER

FASTENER

OFFSET/CLIPPED HEAD STICK NAILS

| | |
|------------------|----------------|
| Collation Angle: | 28 degrees |
| Length: | 2" to 3 1/4" |
| Shank Diameter: | .113" to .131" |
| Head Diameter: | .256" to .303" |
| Collation Type: | Wire, Paper |



SuperLocator

SN438J METAL CONNECTOR NAILER



| FASTENER | |
|-----------------------------|----------------|
| METAL CONNECTOR STICK NAILS | |
| Collation Angle: | 34 degrees |
| Length: | 1 1/2" |
| Shank Diameter: | .131" to .148" |
| Head Diameter: | .280" |
| Collation Type: | Paper |



SuperFinisher®

NF665A/15 15GA. ANGLED FINISH NAILER



| FASTENER | |
|---------------------|------------------|
| ANGLED FINISH NAILS | |
| Length: | 1 1/4" to 2 1/2" |
| Finish Nail: | 15 ga. |



SuperDecking®

CN665D COIL DECKING NAILER



| FASTENER | |
|------------------|------------------|
| COIL NAILS | |
| Collation Angle: | 15 degrees |
| Length: | 1 1/2" to 2 1/2" |
| Shank Diameter: | .092" to .120" |
| Head Diameter: | .224" to .275" |
| Collation Type: | Wire |



SuperFinisher®

NF565A/16 16GA. STRAIGHT FINISH NAILER



| FASTENER | |
|-----------------------|------------------|
| STRAIGHT FINISH NAILS | |
| Length: | 1 1/4" to 2 1/2" |
| Finish Nail: | 16 ga. |



SuperFinisher®

NF255SF2/18 18 GA. BRAD NAILER



| FASTENER | |
|-----------------|----------------|
| BRAD NAILS | |
| Length: | 5/8" to 2 1/8" |
| Shank Diameter: | .041" |
| Head Diameter: | .075" / .051" |
| Collation Type: | 18 ga. |



SuperFinisher®

NF255FA/18 18GA. BRAD NAILER



| FASTENER | |
|----------------------------|----------------|
| BRAD NAILS | |
| Length: | 5/8" to 2 1/8" |
| Head Diameter / Thickness: | .075" / .051" |
| Brad Nail: | 18 ga. |

